



Simcona Electronics
585.328.3230/800.274.6266

Mil-W-16878/1 (Type B)

PVC Insulated .010 wall VW-1 Flame Test
Tin Plated Copper Conductor
Voltage Rating 600 Volts
Temperature Rating -54C to +105C

| Simcona P/N | Gauge | Stranding | M16878/1xxx |
|----------------|-------|-----------|-------------|
| B32-1Txxxx | 32 | Solid | BAA |
| B32-7Txxxx | 32 | 7/40 | BAB |
| B30-1Txxxx | 30 | Solid | BBA |
| B30-7Txxxx | 30 | 7/38 | BBB |
| B28-1Txxxx | 28 | Solid | BCA |
| B28-7Txxxx | 28 | 7/36 | BCB |
| B26-1Txxxx | 26 | Solid | BDA |
| B26-7Txxxx | 26 | 7/34 | BDB |
| B26-19Txxxx | 26 | 19/38 | BDE |
| B24SLDxxxx | 24 | Solid | BEA |
| B24-7Txxxx* | 24 | 7/30 | BEB |
| B24-19Txxxx | 24 | 19/36 | BEE |
| B22SLDxxxx | 22 | Solid | BFA |
| B22-7Txxxx* | 22 | 7/30 | BFB |
| B22-19Txxxx | 22 | 19/34 | BFE |
| B20SLDxxxx | 20 | Solid | BGA |
| B20-7Txxxx | 20 | 7/28 | BGB |
| B20-19/32xxxx* | 20 | 19/32 | BGE |
| B18-7Txxxx | 18 | 7/26 | BHB |
| B18-19Txxxx* | 18 | 19/30 | BHE |
| B16-19Txxxx* | 16 | 19/29 | BJE |
| B14-19Txxxx* | 14 | 19/27 | BKE |

Note items with * are stocking items in standard solid colors

Standard Colors xxxx = color

- 0000 Black
- 1111 Brown
- 2222 Red
- 3333 Orange
- 4444 Yellow
- 5555 Green
- 6666 Blue
- 7777 Violet
- 8888 Gray
- 9999 White